

	Specifications	SR18AJ	SR18A	SR21AJ	SR21A
REACH SPECIFICATIONS	Platform Height	18.0 m		21.0	
	Horizontal Outreach	15.8 m	16.7 m	17.8 m	18.6 m
	Swing	360 degree, continuous		360 degree, continuous	
	Platform Capacity	227 kgs		227 kgs	
	Platform Rotator	180 Grad (90, 90)		180 Grad (90, 90)	
	Jib Range of Articulation	130 degrees (+70,-60)	N/A	130 degrees (+70,-60)	N/A
DIMENSION DATA	A: Platform Size	1.8 m x 0.75 m (Std), 2.4 m x 0.75 m (Opt)		1.8 m x 0.75 m (Std), 2.4 m x 0.75 m (Opt)	
	B: Overall Width	2.46 m		2.46 m	
	C: Tailswing	1.13 m		1.13 m	
	D: Overall Height	2.35 m		2.35 m	
	E: Overall Length	10.04 m	9.17 m	11.57 m	10.15 m
	F: Tumbler center distance	2.575 m		2.575 m	
	G: Ground Clearance	0.425 m		0.425 m	
	Gross Vehicle Weight	12,900 kgs	12,800 kgs	15,200 kgs	14,900 kgs
CHASSIS	Traveling Speed	2.0 km/h		2.0 km/h	
	Gradeability stowed	48 % (26 degrees)		48 % (26 degrees)	
POWER SOURCE	Diesel Engine	Isuzu A 4JB1, PAA-22 (44.3 KW/2,400 rpm)		Isuzu A 4JB1, PAA-22 (44.3 KW/2,400 rpm)	
	Fuel Tank Capacity	150 liter		150 liter	
SAFETY	Standard Features	H-V Control, Travel Speed Control, Rotation Speed Control, Lifting Speed Control, All Motion Alarm, Lever Guard		H-V Control, Travel Speed Control, Rotation Speed Control, Lifting Speed Control, All Motion Alarm, Lever Guard	

SR18AJ / SR21AJ



SR18A / SR21A



Technical specifications may change without notice!

AICHI PLATFORM SERVICE EUROPE BV
Maxwellstraat 50 · NL - 3316 GP Dordrecht
Tel. +31 - (0) 78 - 6550 155 - Fax +31 - (0) 78 - 6550 150
E-mail: info@aichieurope.com - www.aichieurope.com